

Product data sheet

Glass cloth strips 210 g/m²

Technical properties

Parameter	Value	Standard
Weave	Plain	DIN ISO 9354
Weight	206 g/m ² +/- 5%	DIN EN 12127
Yarn		DIN EN 12654
Warp	EC9-68 +/- 5%	
Weft	EC9-68 +/- 5%	
Thread count		DIN EN 1049
Warp	17.2 1/cm +/- 5%	
Weft	12.0 1/cm +/- 5%	
Tensile strength		DIN EN 12654
Warp	500 N/cm	
Weft	350 N/cm	
Combustible mater content	2,00 - 4,00 %	DIN ISO 1887
Fabric thickness	0,18 mm	DIN ISO 4603/E
Length	100 m per roll	
Width	75 mm	
Temperature resistance		
Continual	250 C ⁰	
Temporary	500 C ⁰	



Rockwool A/S
DK-2640 Hedehusene
Tel.: +45 46 56 16 16
Fax: +45 46 56 16 04
E-mail: export@rockwool.dk
Internet: www.rockwool-marine.com

Rockwool Marine & Offshore
Hong Kong Office
Suite 1303, Asia Orient Tower, Town Place
33 Lockhart Road, Wanchai, Hong Kong
Tel: +852 2866 6180
Fax: +852 2866 9555



Rockwool A/S reserves the right to make necessary product changes at any time. Technical specifications are thus stated subject to change.