

Product data sheet

Ovalit T glass fabric adhesive

Product description

Wall covering adhesive

Application

For wallpapering jobs with

- textile wall coverings
 - coarse woven wall coverings
 - metallic wallpapers
 - PVC films with woven backing
 - Velours wallpapers with suede effect
 - As an additive (appr. 20 % to Metylan Spezial)
-

Technical properties

Parameter	Value
Colour	White, dries transparent
Density	1.0 g/cm ³
Temperature range	Do not apply below +10 °C
Form	Ready to use
Storing conditions	Store in dry location, 12 month protect from frost
Dilution	Ovalit T is ready-to-use. If necessary 10 – 20 % wallpaper paste Metylan Special can be added to increase the working time.
Flammability	Hardly flammable acc. to the 1974 International Convention for Safety of Life at Sea (SOLAS) – Marine Professional Association Certificate available



Rockwool A/S
DK-2640 Hedehusene
Tel.: +45 46 56 16 16
Fax: +45 46 56 16 04
E-mail: export@rockwool.dk
Internet: www.rockwool-marine.com

Rockwool Marine & Offshore
Hong Kong Office
Suite 1303, Asia Orient Tower, Town Place
33 Lockhart Road, Wanchai, Hong Kong
Tel: +852 2866 6180
Fax: +852 2866 9555



Rockwool A/S reserves the right to make necessary product changes at any time. Technical specifications are thus stated subject to change.