

Product description

Rockwool Marine Slab 60 is a semi-rigid slab of stone wool. Excellent properties for easy handling and installation.

Application

Marine Slab 60 is primarily used for sound insulation. Perfect in combination as comfort insulation with high noise reduction.




Technical properties

Parameter	Value	Standard
Thermal conductivity	$\lambda_{10} = 0,034 \text{ W/mK}$	EN 12667
Nominal density	60 kg/m ³	-
Compressive strength	-	EN 826
Fire classification	Non-combustible	IMO A.799(19)
Water absorption (short term)	<1 kg/m ²	EN 1609 AC
Max. service temp.	Wool 250°C	-
Sound absorption directly mounted	$\alpha_w = 0,85$ Thickness: 50 mm	ISO 354 (approximated) Evaluated after ISO 11 654
Facings	-	IMO A.653(16) (low flame - spread)
Dimensions	Marine Slab 60: L: 1000 mm - W: 600 mm - T: 50 mm	



Rockwool A/S
 DK-2640 Hedehusene
 Tel.: +45 46 56 16 16
 Fax: +45 46 56 16 04
 E-mail: export@rockwool.dk
 Internet: www.rockwool-marine.com

Rockwool Marine & Offshore:
 Hong Kong Office
 Suite 1303, Asia Orient Tower, Town Place
 33 Lockhart Road, Wanchai, Hong Kong
 Tel: +852 2866 6180
 Fax: +852 2866 9555



Rockwool A/S reserves the right to make necessary product changes at any time. Technical specifications are thus stated subject to change.