


### Product description

Rockwool Marine Slab 60 Black is a semi-rigid slab of stone wool. The black tissue gives a dust free surface. Excellent properties for easy handling and installation.

#### Application

Marine Slab 60 Black is primarily used for ventilation duct insulation. The product is a perfect combination for thermal insulation with high noise reduction.




### Technical properties

Parameter	Value	Standard
<b>Thermal conductivity</b>	$\lambda_{10} = 0,034 \text{ W/mK}$	EN 12667
<b>Nominal density</b>	60 kg/m <sup>3</sup>	-
<b>Compressive strength</b>	-	EN 826
<b>Fire classification</b>	Non-combustible	IMO A.799(19)
<b>Water absorption (short term)</b>	<1 kg/m <sup>2</sup>	EN 1609
<b>Max. service temp.</b>	Wool: 250°C Facing: 80°C	-
<b>Sound absorption directly installed</b>	$\alpha_w = 0,85$	ISO 354 (approximated) Evaluated after ISO 11 654
<b>Facings</b>	Black glass tissue	MED-B-4185 IMO A.653(16) (low flame - spread)
<b>Dimensions</b>	Marine Slab 60 Black: L: 1000 mm - W: 600 mm - T: 25 mm	



Rockwool A/S  
DK-2640 Hedehusene  
Tel.: +45 46 56 16 16  
Fax: +45 46 56 16 04  
E-mail: export@rockwool.dk  
Internet: www.rockwool-marine.com

Rockwool Marine & Offshore:  
Hong Kong Office  
Suite 1303, Asia Orient Tower, Town Place  
33 Lockhart Road, Wanchai, Hong Kong  
Tel: +852 2866 6180  
Fax: +852 2866 9555



Rockwool A/S reserves the right to make necessary product changes at any time. Technical specifications are thus stated subject to change.