

Rockwool Marine Slab 80 Black

Product description

Rockwool Marine Slab 80 Black is a semi-rigid slab of stone wool. The black tissue gives a dust free surface. Excellent properties for easy handling and installation.

Application

Marine Slab 80 Black is generally developed for sound insulation. The product can also be used as finishing surface in areas where the surface just needs to be dust free. Another applications can be behind perforated plates in panels or similar.




Technical properties

Parameter	Value	Standard
Thermal conductivity	$\lambda_{10} = 0,034 \text{ W/mK}$	EN 12667
Nominal density	80 kg/m ³	-
Compressive strength	-	EN 826
Fire classification	Non-combustible	IMO A.799(19)
Water absorption (short term)	<1 kg/m ²	EN 1609
Max. service temp.	Wool: 250°C Facing: 80°C	-
Sound absorption directly installed	$\alpha_w = 0,9$ Thickness: 50 mm	$\alpha_w = 0,95$ Thickness: 2x50 mm
Facings	Black glass tissue	ISO 354 (approximated) Evaluated after ISO 11 654 MED-B-4185 IMO A.653(16) (low flame - spread)
Dimensions	Marine Slab 80 Black: L: 1000 mm - W: 600 mm - T: 50 mm	



Rockwool A/S
DK-2640 Hedehusene
Tel.: +45 46 56 16 16
Fax: +45 46 56 16 04
E-mail: export@rockwool.dk
Internet: www.rockwool-marine.com

Rockwool Marine & Offshore:
Hong Kong Office
Suite 1303, Asia Orient Tower, Town Place
33 Lockhart Road, Wanchai, Hong Kong
Tel: +852 2866 6180
Fax: +852 2866 9555



Rockwool A/S reserves the right to make necessary product changes at any time. Technical specifications are thus stated subject to change.